



Technical polymer, nickel-plated
brass, NBR



| ØD | C |  | F | G | H | L/2 | kg |
|----|------|---|----|------|------|------|-------|
| 4 | R1/8 | 3108 04 10 | 10 | 8.5 | 15.5 | 14 | 0.006 |
| | R1/4 | 3108 04 13 | 14 | 8.5 | 16 | 14 | 0.015 |
| 6 | R1/8 | 3108 06 10 | 10 | 10.5 | 17.5 | 16 | 0.007 |
| | R1/4 | 3108 06 13 | 14 | 10.5 | 18 | 16 | 0.016 |
| 8 | R1/8 | 3108 08 10 | 10 | 13.5 | 22 | 23 | 0.009 |
| | R1/4 | 3108 08 13 | 14 | 13.5 | 21 | 23 | 0.016 |
| | R3/8 | 3108 08 17 | 17 | 13.5 | 21 | 23 | 0.020 |
| 10 | R1/4 | 3108 10 13 | 15 | 16 | 24 | 26.5 | 0.017 |
| | R3/8 | 3108 10 17 | 17 | 16 | 24 | 26.5 | 0.022 |
| | R1/2 | 3108 10 21 | 21 | 16 | 24 | 26.5 | 0.033 |
| 12 | R1/4 | 3108 12 13 | 15 | 19 | 27 | 31 | 0.021 |
| | R3/8 | 3108 12 17 | 17 | 19 | 27 | 31 | 0.026 |
| | R1/2 | 3108 12 21 | 21 | 19 | 27 | 31 | 0.037 |
| 14 | R3/8 | 3108 14 17 | 20 | 22 | 30.5 | 35 | 0.038 |
| | R1/2 | 3108 14 21 | 24 | 22 | 28.5 | 35 | 0.048 |
| 16 | R3/8 | 3108 16 17 | 27 | 27 | 53 | 38.5 | 0.128 |
| | R1/2 | 3108 16 21 | 27 | 27 | 53 | 38.5 | 0.124 |

Pre-coated thread

The body swivels for positioning purposes.