



Technical polymer, nickel-plated  
brass, NBR



	ØD	C		F	G	H	L	kg
4	R1/8	3109 04 10		10	8.5	13.5	14	0.006
	R1/4	3109 04 13		14	8.5	14	14	0.015
	R3/8	3109 04 17		17	8.5	13.5	14	0.018
6	R1/8	3109 06 10		10	10.5	15.5	16	0.006
	R1/4	3109 06 13		14	10.5	16	16	0.015
	R3/8	3109 06 17		17	10.5	16	16	0.019
8	R1/2	3109 06 21		21	10.5	16.5	16	0.034
	R1/8	3109 08 10		10	13.5	19	23	0.007
	R1/4	3109 08 13		14	13.5	18	23	0.014
10	R3/8	3109 08 17		17	13.5	18	23	0.018
	R1/2	3109 08 21		21	13.5	19.5	23	0.033
	R1/8	3109 10 10		15	16	23	26.5	0.012
12	R1/4	3109 10 13		15	16	22	26.5	0.014
	R3/8	3109 10 17		17	16	22	26.5	0.019
	R1/2	3109 10 21		21	16	22	26.5	0.031
14	R1/4	3109 12 13		15	19	25	31	0.016
	R3/8	3109 12 17		17	19	25	31	0.022
	R1/2	3109 12 21		21	19	25	31	0.033
16	R3/8	3109 14 17		20	22	30.5	35.5	0.031
	R1/2	3109 14 21		24	22	28.5	35.5	0.041
	R3/8	3109 16 17		27	27	53	39	0.106
	R1/2	3109 16 21		27	27	53	39	0.104

Pre-coated thread

The body swivels for positioning purposes.