





Nickel-plated brass, NBR



	$\varnothing D$	C		F1	F2	H	kg
4	R1/8	3175 04 10		10	3	9.5	0.005
	R1/4	3175 04 13		14	3	6.5	0.012
	R3/8	3175 04 17		17	3	8	0.024
6	R1/8	3175 06 10		10	4	11.5	0.005
	R1/4	3175 06 13		14	4	8.5	0.011
	R3/8	3175 06 17		17	4	8.5	0.022
8	R1/2	3175 06 21		21	4	9	0.043
	R1/8	3175 08 10		13	5	20	0.011
	R1/4	3175 08 13		14	6	17	0.014
	R3/8	3175 08 17		17	6	13	0.021
10	R1/2	3175 08 21		21	6	12	0.040
	R1/8	3175 10 10		16	5	22.5	0.017
	R1/4	3175 10 13		16	7	20	0.017
12	R3/8	3175 10 17		17	8	16.5	0.019
	R1/2	3175 10 21		21	8	14	0.037
	R1/4	3175 12 13		19	7	26.5	0.029
14	R3/8	3175 12 17		19	9	24	0.028
	R1/2	3175 12 21		21	10	19.5	0.036
16	R3/8	3175 14 17		22	9	28.5	0.043
	R1/2	3175 14 21		24	10	23.5	0.047
16	R3/8	3175 16 17		27	9	32.5	0.068
	R1/2	3175 16 21		27	12	32.5	0.079

Pre-coated thread